

Style: K**Guide Specification**

Milcor K Access Doors provide critical service access in plaster walls or ceilings. Sizes are as indicated on page 6.

Material

16-gauge steel frame with 14-gauge door panel and 22-gauge galvanized perimeter casing beads.

Finish

Steel is chemically bonded with a gray prime coat of baked-on electrostatic powder. Brilliant white, gold sand and jet black finishes are also available.

Hinge

Concealed spring hinges allow panel to open to 175 degrees. Panels are removable by taking pin out of hinge leaf attached to panel. Number of hinges varies with size of door.

Lock

Flush, screwdriver-operated with steel cam. Available with allen head or spanner head or mortise cylinder lock on special order. Cylinder lock, with 2 keys furnished replacing one cam lock, is available at a slight extra charge.

Packing

One per carton.

Style: DWR**Guide Specification**

Milcor DWR Access Doors provide critical access in drywall ceilings while keeping maintaining ceiling appearance. Sizes are as indicated on page 7.

Material

16-gauge galvanized steel frame with drywall bead. 18-gauge galvanized steel door panel recessed for installation of a drywall panel. 24" x 24" and larger panels reinforced.

Finish

Steel is chemically bonded with a prime coat of gray baked-on electrostatic paint.

Hinge

Continuous hinge is steel with stainless steel pin, mounted on the long side.

Lock

Flush, screwdriver-operated with steel cam. Available with allen head or spanner head lock on special order. Cylinder lock, with 2 keys furnished replacing one cam lock, is available at an extra charge.

Packing

One per carton.

Style: AP**Guide Specification**

Milcor AP Access Doors provide critical access in acoustical plaster ceilings while keeping acoustical surfaces intact maintaining ceiling appearance. Sizes are as indicated on page 8.

Material

16-gauge galvanized steel frame with plaster lathe. 18-gauge galvanized steel door panel with plaster lathe bonded to recessed cover. 24" x 24" and larger panels reinforced.

Finish

Steel is chemically bonded with a prime coat of gray baked-on electrostatic paint.

Hinge

Continuous hinge is steel with stainless steel pin, mounted on the long side on 12" x 24" and 24" x 36" sizes.

Lock

Flush, screwdriver-operated with steel cam. Available with allen head or spanner head lock on special order. Cylinder lock, with 2 keys furnished replacing one cam lock, is available at an extra charge.

Packing

One per carton.