



**STANDARD RETROFIT SAFETY RAILING COMPATIBILITY:**  
 (NOMINAL HATCH WIDTH X LENGTH)  
 33" X 30.5" - MINIMUM  
 58" X 52" - MAXIMUM

RAIL HEIGHT MEETS 42" REQUIREMENT

DISPLAYED DIMENSIONS ARE OUTSIDE DIMENSIONS OF CURB, NOT NOMINAL.

SAFETY RAIL TO BE ATTACHED SO THAT GATE EXITS OPPOSITE THE HINGED SIDE OF THE ROOF HATCH.

- FEATURES:**
1. SELF CLOSING HINGES
  2. POWDER COATED SAFETY YELLOW
  3. SLOTTED CORNER BRACKET HOLES FOR UNIVERSAL COMPATABILITY AND EASE OF INSTALLATION
  4. RAIL AND GATE TELESCOPE TO ACCOMODATE MULTIPLE HATCH SIZES.

ORDER WILL NOT BE RELEASED FOR FABRICATION UNTIL SIGNED COPY IS RECEIVED.

VERIFICATION AND APPROVAL OF GENERAL ARRANGEMENT AND OVERALL DIMENSIONS FOR THIS DOCUMENT ARE REQUIRED BEFORE THE ORDER IS ENTERED FOR MANUFACTURING.

APPROVAL SIGNATURE \_\_\_\_\_

TITLE HELD \_\_\_\_\_

DATE OF APPROVAL \_\_\_\_\_

DRAWN	JCS	12/2/2020	Hart & Cooley Inc. 5030 Corporate Exchange Blvd. SE Grand Rapids, MI. 49512 Ph: 800-624-8642		
CHECKED		<b>MILCOR</b>	TITLE		
QA		TOLERANCE UNLESS SPECIFIED	RETROFIT SAFETY RAIL		
MFG		.XXX ± 0.005"	SIZE	DWG NO	REV
APPROVED		.XX ± 0.01"	D	MSTR-30-52_SUB	A
		FRACT. ± 1/16"	SCALE		
		ANGLES ± 1'			SHEET 1 OF 1